

Prince George Loader Ticket

Prince George Loader Ticket - Gehl articulated loaders have been manufactured to fit just about any condition. They offer optimal maneuverability and great traction due to a heavy-duty oscillating joint which offers 45-degree rotating angles right and left, along with 10 degrees of oscillating in both directions. Access is granted to tight and confined places by narrow engine widths. Majority of skid-steer loaders with similar operating capacities are unable to compete. The tires and bucket on the Gehl machine follow a constant turn radius also. This means the rear tires of the loader follow the trail of the front tires.

Fantastic hydraulic performance, along with several time-saving features on the Gehl articulated loaders, provides customers with the hydraulic precision and power they have come to expect from all the Gehl machines. Bucket float and lift arm features allow these machines to execute light scraping and rearward leveling actions. Flat-face couplers, together with the two easily reachable auxiliary hydraulic lines power many tools and make changing the accessories a simple job to complete.

The articulated loaders made by Gehl have lift arms which are uniquely created for great visibility, fast time cycle and to maximize strength. The linkage pattern is specialized to allow for mechanical self-leveling action in down and up directions. It can also easily carry out excellent bucket dump angles at the top and mid ranges of the hoist path as well as providing excellent forward reach. Models 140 and 340 have parallel type linkage and the 540 model has "Z" bar kind linkage. These linkage layouts provide great bucket breakout forces from 2433lbs on the model 140 to ten thousand seven hundred forty nine pounds on the 540 model.

Known all over the globe for their ease of operation, Gehl articulated loaders provide supreme ergonomics and excellent visibility. The models 340 and 540 have closed cabs options presented. This offers comfort and safety for the individual operating it. Secure operation and 360 degree visibility is maintained by placing the individual operating it higher than the load to ensure an excellent viewpoint of the attachment. An inching pedal allows the person operating it to vary ground speed while maintaining a fixed engine velocity. This feature enables the operator to properly run attachments while ensuring precise engine velocity control. A multi-function direction control controls the travel direction, float, differential lock and auxiliary hydraulic functions, bucket and the lift arm.