## **Prince George Scissor Lift License**

Prince George Scissor Lift License - The is an inherent risk in operating a scissor lift, since with all types and kinds of powered work tools will require correct handling to be able to prevent accidents that can result in injuries or damage. Companies have to ensure that staff using this particular machinery have the necessary training.

Unqualified personnel should not be permitted by their companies to use scissor lifts. The lift is designed to raise materials and people to various heights. Failure to know and completely follow safety standard could cause injuries for the users or damage to the lift.

There are no rules governing the use of fall protection for scissor-lift users. Nonetheless, manufacturers could recommend the use of fall protection and in various situations tying off in scissor lifts may be required by employer guidelines, job-specific risk assessments or local regulations.

In order to ensure that the scissor lift is in good working condition before utilizing the machinery, the operator needs to perform a thorough check. This is the operator's task, even though the unit has already been in service that day. The machine's operator's handbook contains a pre-operation checklist.

The things that an operator should look for when performing a scissor lift inspection, consists of checking tire-inflation pressure, and checking platform controls and ground controls to make sure they are working. Look for any delayed movement on the fly section when the boom is extending and retracting since this can indicate some cables are loose. While operating the controls, make sure that the emergency stop switches are working. Operate functions against the equipment's cutout switches. Test the boom control system by cycling a boom lift to the furthest extent of its operating envelope. Safety limiters must automatically stop the unit before it moves into an unstable position, if they are functioning right. If they aren't, turn off the lift and make sure that repairs are made before it is used again.

Safe operating measures should be followed always, with the levers being operated with even, controlled pressure. A control lever must never be pushed from one position to the opposite position. The lever must be shifted to neutral, before stopping, and afterward proceeding in the desired direction. When released, control switches and levers must return to the neutral position automatically. Depress the foot switch before operating platform controls.